

WetShield – Wet Look Stone and Tile Sealer

TECHNICAL DATASHEET

COMPOSITION

Advanced formulation of modified polysiloxanes combined with specialized additives, designed with solvent-free technology.

TECHNICAL DATA

- ✔ Appearance: Clear, liquid
- ✔ Active Ingredient: Approx. 6%

Key Features

- ✔ Provides a wet-look finish on natural stones and matt-finish vitrified tiles
- ✔ Highly water-repellent and resistant to varying weather conditions
- ✔ Forms a strong, penetrating, and visible protective layer
- ✔ Suitable for marble, natural stones, and engineered stones

STORAGE

- ✔ Store between 0°C and 40°C.
- ✔ Avoid exposure to frost or extreme heat.
- ✔ If storage conditions are compromised, verify product usability before application.

Coverage

Approximately 40–200 sq. ft. for two coats, depending on the porosity and texture of the surface.

Durability

- ✔ Interior Surfaces: 2–3 years
- ✔ Exterior Surfaces: 1–2 years
- ✔ For surfaces exposed to heavy use, annual resealing is recommended.

Shelf Life

12 months from the date of manufacturing when stored in original, sealed packaging.

Warning

Flammable Material: Handle with care and keep away from sources of ignition.



APPLICATION INSTRUCTIONS

- ✔ Mask and protect areas that are not intended for treatment.
- ✔ Ensure the surface is clean, dry, and free from oil, grease, and dampness.
- ✔ Wear gloves during application and ensure good ventilation.
- ✔ Apply a liberal, even coat using a cotton cloth over the target surface.
- ✔ Allow the sealer to penetrate, then thoroughly wipe off any excess with clean, dry towels.
- ✔ For porous or highly absorbent surfaces, apply a second coat after 15 minutes, repeating steps 4 and 5.
- ✔ After final application, wipe again with dry towels to remove all residual sealer.
- ✔ Full curing is achieved within 24–48 hours. Light foot traffic can resume after 6–8 hours. If early use is necessary, protect the surface with red rosin paper until fully cured.
- ✔ The material has an open pot life of approximately 20 minutes once exposed to air.

Attention

The information provided is based on thorough research and practical experience. However, it does not constitute a legally binding assurance of specific properties.

Users are advised to conduct preliminary tests to confirm product suitability for their intended use.

Detailed protective measures can be found in the product's Safety Data Sheet (SDS).

Packaging

Available in 30 Ltr Carboys.